

P. L. C Trainer (Basic Type)



01

02

03

04

Specification

■ WSB-MP83P

- P. L. C Unit
 - LS - XGB
- P. L. C Input
 - Input : 16 Points
 - Sink & Source Type
- P. L. C Output
 - Output : 16 Points
 - Relay Type

■ WSB-MP89P

- P. L. C Unit
 - Mitsubishi - FXSeries
- P. L. C Input
 - Input : 16 Points
 - Sink Type
- P. L. C Output
 - Output : 16 Points
 - Relay Type

■ WSB-MP88P

- P. L. C Unit
 - Siemens - S7(1200)
- P. L. C Input
 - Input : 14 Points
 - Source Type
- P. L. C Output
 - Output : 10 Points
 - TR Source Type

■ Main Controller

- Main Voltage : 1 Phase 220~240V / 50~60Hz
- DC Output : DC 24V
- Input Switch & Output Lamp & Buzzer
- Proximity & Photo Sensor
- DC Motor
- Digital Switch(0000 ~ 9999) & Seven Segment (0000 ~ 9999)

Accessory

- Experiment Manual : 1Copy
- Power Cable : 1EA
- Test Lead (Banana Plug) : 1Unit
- Program Tool : 1Copy
- Communication Cable : 1EA
- Dust Cover : 1EA

Option

- Demonstration Unit : 1Set